

MERIDIAN G SERIES CONTROL UNIT
AND RECEIVER
INSTALLATION GUIDE



G Series Control Unit and Receiver Installation Guide

Important safety instructions

- Read the instructions.
- Keep these instructions.
- Follow all instructions.
- Do not use this apparatus near water.
- Clean only with a dry cloth.
- Install only in accordance with the manufacturer’s instructions.
- Refer all servicing to approved service personnel.

WARNING: TO REDUCE THE RISK OF FIRE OR ELECTRIC SHOCK, DO NOT EXPOSE THIS APPARATUS TO RAIN OR MOISTURE

Safety warnings

- Do not expose the product to dripping or splashing.
- Do not place any object filled with liquid, such as a vase, on the product.
- Do not place naked flame sources, such as lighted candles, on the product.

To avoid interference

Do not position the product:

- Near strong magnetic radiation, such as near a power amplifier.
- Near to a television, or where connecting cables may be subject to or cause interference.

To avoid overheating

- Leave at least 10cm around the equipment to ensure sufficient ventilation.

Do not position the product:

- In direct sunlight.
- Near heat sources, such as a radiator.
- Directly on top of heat producing equipment, such as a power amplifier.
- On a soft surface, such as a carpet, which would obstruct the ventilation holes in the base.

The product normally runs warm to the touch.

Radio interference

FCC Warning: This equipment generates and can radiate radio frequency energy and if not installed and used correctly in accordance with our instructions may cause interference to radio communications or radio and television reception. It has been type-tested and complies with the limits set out in Subpart J, Part 15 of FCC rules for a Class B computing device. These limits are intended to provide reasonable protection against such interference in home installations.

EEC: This product has been designed and type-tested to comply with the limits set out in EN55013 and EN55020.



Contents

Introduction	1
Provides information about the available control unit and receiver models, a description of each product, and technical specifications.	
Control unit and receiver models	1
Specifications	4
Installing the control unit or receiver	5
Describes how to install the control unit or receiver and connect it to the other equipment in your system.	
Unpacking	5
Audio connections	6
Tuner (G01/G51 only) and communications connections	13
Configuring the control unit or receiver	17
Explains how to configure the control unit or receiver using the front-panel controls.	
Configuration Wizard	17
Stage 1: Resetting the product	18
Stage 2: Configuring sources	19
Stage 3: Configuring other settings	21
Configuring the sensitivity of each source	23
Troubleshooting	25
Provides suggested solutions to problems while installing, configuring, or operating the product.	
Maintenance	28
Service and guarantee	29
Index	31

Copyright and acknowledgements

Sales and service in the UK

Meridian Audio Ltd
Latham Road
Huntingdon
Cambridgeshire
PE29 6YE
England

Tel +44 (0)1480 445678
Fax +44 (0)1480 445686

World Wide Web – <http://www.meridian-audio.com/>

Copyright © 2003-2004 Meridian Audio Ltd

Designed and manufactured in the UK by Meridian Audio Ltd. Meridian Audio reserves the right to make changes and improvements to any of the products described in this document without prior notice.

Part no: GCU/2

Sales and service in the USA

Meridian America Inc
8055 Troon Circle
Suite C
Austell
GA30168-7849
USA

Tel +1 (404) 344 7111
Fax +1 (404) 346 7111

Boothroyd|Stuart Meridian, Meridian, and Meridian Digital Theatre are registered trademarks of Meridian Audio Ltd.

This guide was produced by Human-Computer Interface Ltd, <http://www.interface.co.uk/>

Introduction

This guide provides full information about unpacking the control unit or receiver, connecting it to the other equipment in the system, and configuring it using the front panel.

Once you have connected and configured the product, refer to the *G Series System Guide* for information about operating it.

Control unit and receiver models

This Installation Guide applies to the G01 Control Unit, G02 Balanced Control Unit, and G51 Receiver. The main differences between each of these products are given in the following table:

Product	Preamplifier	Power amplifier	Tuner
G01	Stereo	No	Yes
G02	Dual mono/balanced	No	No
G51	Stereo	100W stereo	Yes

G01 Control Unit

The Meridian G01 is a fully-integrated analogue control unit which includes a tuner module. It is an ideal complement to the G Series power amplifiers.

Incorporating both a preamplifier and controller, the G01 Control Unit provides seven stereo analogue inputs plus an AM/FM or DAB/FM tuner. The AM option provides LW/MW reception, and the FM stage provides VHF stereo band II reception with RDS. The inputs are nominally designated Aux (phono), CD, TV, Tape, Disc, DVD, and VCR.

Two sets of stereo tape outputs are provided, along with two preamp output pairs, allowing maximum flexibility in the configuration of tape/decoder loops, multi-room, and amplification/bi-amplification. In addition to the main outputs, a stereo headphone socket is provided on the back panel for personal listening.

G02 Balanced Control Unit

The Meridian G02 is a true dual-mono analogue control unit/preamplifier with an extremely high-quality power supply for ultra-low noise and distortion. Featuring a fully-balanced signal path throughout, it is an ideal complement to the G Series power amplifiers and is particularly suited to those who wish to maintain a balanced analogue signal path at the very highest quality of reproduction.

Balanced operation has always been preferred in the professional audio industry, as it can significantly reduce hum and noise and make the system less prone to interference. The G02 brings this philosophy to the G Series. Incorporating both a preamplifier and controller, the G02 Balanced Control Unit provides seven two-channel analogue inputs. Four of these – nominally designated Aux (phono), Radio, TV, and VCR – are unbalanced, while the remaining three – CD, Tape, and Disc – offer balanced inputs on XLR connectors.

The internal architecture of the G02 is balanced throughout, and the first thing that happens to an unbalanced input is electronic balancing for maximum quality throughout the signal chain.

Two sets of unbalanced stereo tape outputs are included on the back panel, allowing maximum flexibility in the configuration of tape/decoder loops and multi-room capabilities. The outputs can be configured as a single balanced output by using a suitable break-out cable.

Two sets of main outputs are provided: the primary outputs are balanced on XLR male connectors, while unbalanced outputs are also included on phono connectors.

G51 Receiver

Incorporating a preamplifier, controller, and a power amplifier that features a unique low-feedback topology and extremely low output impedance, the G51 Receiver provides seven stereo analogue inputs plus an AM/FM or DAB/FM tuner. The AM option provides

LW/MW reception, and the FM stage provides VHF stereo band II reception with RDS. The inputs are nominally designated Aux (phono), CD, TV, Tape, Disc, DVD, and VCR.

Two sets of stereo tape outputs are provided, along with two preamp out pairs, one of which is normally jumpered to the adjacent power amplifier input sockets. This allows, for example, a bi-amped configuration with an additional two-channel amplifier such as the G56.

The two-channel amplifier includes the latest power amp developments from Meridian, used in the flagship DSP8000 digital loudspeaker systems.

The amplifiers feature active bias control throughout, with thermal sensing that carefully manages the temperature and current flow at different volume levels. Fully DC-coupled, the signal path contains no unnecessary capacitors, while those in the power supplies are audiophile grade components.

The amplifiers are of a unique low-feedback design for minimum transient and interface intermodulation distortion, offering superb clarity and transparency right across the audible range, with an output impedance that is close to zero and delivers a solid 100W continuous mean power per channel into 8Ω suitable for virtually any high-quality passive loudspeaker system.

The amplifier, when in standby mode, maintains a standing voltage on the power rails, reducing the time taken for optimum

performance to be delivered after power-up from tens of minutes to a few seconds.

Two sets of outputs per channel are provided on sturdy binding posts colour-coded for easy reference. The output terminals are connected to the amplifiers by Van den Hul silver-strand cable to minimise signal loss.

In addition to the main outputs, a stereo headphone socket is provided on the back panel for personal listening, in conjunction with a 'speaker off' facility.

General

Each of the products provides a front-panel volume knob (press to mute), which activates a specially-designed dual differentially-balanced volume control circuit. This ensures perfect stereo tracking and full frequency range performance at all volume levels.

In all products the sensitivity of each input can be individually adjusted as desired.

The Aux input can be configured for either moving coil or moving magnet cartridge operation by the addition of appropriate phono modules.

All phono connectors are gold plated for maximum transparency.

Specifications

	G51	G01	G02
Distortion	Less than 0.002%.	Less than 0.002%.	Less than 0.002%.
Signal/Noise	Better than –96dB (2V output) for normal inputs. Better than –70dB for MM input, –60dB for MC input.	Better than –96dB (2V output) for normal inputs. Better than –70dB for MM input, –60dB for MC input.	Better than –100dB (2V output) for normal inputs. Better than –70dB for MM input, –60dB for MC input.
MM option	Sensitivity adjustable 0.5–3mV for 5cm/s @ 1kHz. Overload point 47mV @ 1kHz. Cartridge load 47k Ω + 100pF.		
MC option	Sensitivity adjustable 38–1200 μ V for 5cm/s @ 1kHz. Cartridge load 220 Ω + 10nF.		
Inputs	7 unbalanced phono inputs, 0.5-2.5V RMS, 4 sensitivity settings, impedance 20k Ω .	7 unbalanced phono inputs, 0.5-2.5V RMS, 4 sensitivity settings, impedance 20k Ω .	4 unbalanced phono inputs, 3 balanced XLR, 0.5-2.5V RMS per output, 4 sensitivity settings, impedance 20k Ω .
Outputs	2 outputs 100W per channel into 8 Ω , 160W per channel into 4 Ω . Volume control 99 steps of 1dB.	2 unbalanced phono outputs, 0–3V RMS maximum. Impedance 47 Ω .	1 unbalanced, phono outputs, 0–3V RMS. 1 balanced XLR output, 0–6V RMS. Impedance 47 Ω .
Tape outputs	2 unbalanced outputs 1.5V RMS, impedance 470 Ω .	2 unbalanced outputs 1.5V RMS, impedance 470 Ω .	2 unbalanced outputs 1.5V RMS, impedance 470 Ω .
Headphone	2V RMS maximum output.	2V RMS maximum output.	None.
Tuner	DAB: Band III and L Band. AM: Long/Medium wave, 150-285/525-1605kHz. FM: VHF Band II, 87.5-108MHz, sensitivity 1.5 μ v.		None.
Trigger output	12VDC.	12VDC.	8VDC.
Comms	2 5-pin 240° DIN sockets, BNC socket, RS232 interface.		
Construction	Meridian black or silver finish.	Meridian black or silver finish.	Meridian black or silver finish.
Dimensions	440mm x 90mm x 350mm (17.32" x 3.54" x 13.78") WHD.		
Weight	13kg (29lbs) approx.	8.5kg (19lbs) approx.	8.5kg (19lbs) approx.
Controls	Front-panel soft keys include control of Source, Copy, Mute, Display, etc. Power button, volume control. Full remote control of all features via MSR+.		
Display	Multi-character dot-matrix Vacuum Fluorescent Display.		

Installing the control unit or receiver

This chapter explains how to install the control unit or receiver. It describes what you should find when you unpack the product, and how you should connect it to the other equipment in the system.

You should not make any connections to the product or to any other component in the system while the AC power supply is connected and switched on.

Unpacking

The G01 Control Unit, G02 Balanced Control Unit, and G51 Receiver are supplied with the following accessories:

- MSR+ remote control with batteries, manual, and spare key caps.
- Meridian Comms lead.
- Pre-Power jumpers preinstalled (G51 only).
- Power cord.
- This manual.
- *Meridian G Series System Guide*.

Models fitted with an AM/FM tuner also include the following:

- AM antenna (G01 and G51).
- FM antenna (G01 and G51).
- 2 FM antenna (Belling-Lee) adaptors (G01 and G51).

Models fitted with a DAB/FM tuner also include the following:


- Telescopic DAB antenna.

If any of these items are missing please contact your dealer.

Note: You should retain the packaging in case you need to transport the unit.

Audio connections

G01 Control Unit



Use this connector

ANALOGUE IN A1 to A7

COPY OUT

PRE OUT

HEADPHONE

To connect to this


The analogue outputs of a DVD player, tape recorder, TV tuner, CD player, or similar source.

The analogue inputs of a tape recorder or second-zone system.

The analogue inputs of a power amplifier or analogue active loudspeakers.

Headphones of between 8Ω and 15Ω fitted with a stereo $\frac{1}{4}$ " jack plug.

G02 Balanced Control Unit



Use this connector


- ANALOGUE IN A1 to A4
- ANALOGUE IN A5 to A7
- COPY OUT
- MAIN OUT

To connect to this

- The unbalanced analogue outputs of a source such as a radio tuner, VCR, or TV tuner.
- The balanced analogue outputs of a source such as a CD player.
- The analogue inputs of a tape recorder or second-zone system.
- The balanced or unbalanced inputs of a power amplifier or analogue active loudspeakers.

G51 Receiver

The G51 Receiver integrates a preamplifier and power amplifier, and it provides preamplifier outputs and power amplifier inputs to allow these stages to be used independently, or together using the jumpers provided.



Use this connector

ANALOGUE IN A1 to A7

COPY OUT

PRE OUT

AMP IN

HEADPHONE

Loudspeaker outputs

To connect to this

The analogue outputs of a source such as a tape recorder, TV tuner, or CD player.


The analogue inputs of a tape recorder or second-zone system.

The power amplifier input, and an optional additional power amplifier.

The PRE OUT using the jumpers fitted.

Headphones of between 8Ω and 15Ω fitted with a stereo $\frac{1}{4}$ " jack plug.


Loudspeakers of 2Ω to 16Ω .

To connect to an analogue source (eg G07 24-bit CD Player)


You can connect up to seven analogue sources to the G Series control unit or receiver.

- If the source is a Meridian product connect together the COMMS sockets using the Comms lead provided.

- Connect the analogue source to one of the analogue input sockets using a pair of phono leads.

To connect the G02 to a source with balanced outputs (eg G08 24-bit Upsampling CD Player)


- Connect the BALANCED outputs from the G08 to the A5 (CD) balanced input on the G02, using XLR leads.
- If the source is a Meridian product connect together the COMMS sockets using the Comms lead provided.

To connect to a turntable


The A1 (AUX) input can be fitted with a moving coil or moving magnet input stage. Contact your dealer for details.

- Connect the turntable ground connection to the TECHNICAL GROUND terminal, to avoid hum

- Connect the cartridge output to the A1 AUX input.

To connect to a tape recorder

- Connect one pair of COPY OUT sockets from the G01/G02/G51 to the analogue record input on the tape recorder using a pair of phono leads.
- Connect the analogue monitor output from the tape recorder to the A4 TAPE input on the G01/G51 or input A6 on the G02 using a pair of phono leads.


To connect a second-zone system

The G01, G02, or G51 makes an ideal controller for a second zone. You can connect it to the COPY or ZONE OUT of the controller in the main room to allow you to copy a source from the main room to the second zone.


- Connect one pair of COPY or ZONE OUT sockets from the controller in the main room (eg G01, G02, or G68) to the A4 TAPE inputs on the second-zone controller.

- Connect the COMMS sockets using the Comms lead provided.
- Configure the control unit or receiver in the second zone to the Type setting for a second zone; see *Stage 1: Resetting the product*, page 18.

For more information see the *Meridian Three Room Plus* guide at www.meridian-audio.com.

To connect the G01 to an unbalanced power amplifier or active analogue loudspeakers (eg Meridian M33s)

- Connect the PRE OUT sockets from the G01 to the inputs of a power amplifier, or to active analogue loudspeakers such as the Meridian M33s.


To connect the G02 to a balanced power amplifier (eg Meridian G56 or G57 Two-channel Power Amplifier)

- Connect the BALANCED MAIN OUT sockets from the G02 to the balanced inputs of the power amplifier.

To connect the G51 to loudspeakers


The G51 Receiver provides two pairs of outputs for each channel so you can bi-wire separately to the bass/mid and treble drivers in each speaker, for higher quality.

Alternatively, a single pair of loudspeaker cables can be used for each channel.

To bi-wire the G51 to loudspeakers

- Connect one pair of + and – terminals from the right-channel outputs of the G51 to the treble input of the right loudspeaker, checking the orientation of the + and – connections carefully.
- Connect the other pair of + and – terminals from the right-channel outputs of the G51 to the bass/mid inputs of the right loudspeaker.
- Connect the left channel to the left loudspeaker in the same way.

Tuner (G01/G51 only) and communications connections

**Use this connection**

DIN COMMS

BNC COMMS

RS232 connection

USB connection

IR IN

ANTENNA FM, AM, or DAB/FM

TRIGGER OUTPUT

To connect to this

Other Meridian G Series, 500 Series, or 800 Series equipment, or Meridian DSP loudspeakers.

Future Meridian components.


A computer, for configuring the control unit or receiver.

A computer, in future applications.

A G12 IR Receiver, or approved alternative infra-red repeater. Contact your dealer for details.

FM and AM or DAB/FM antennae (not applicable to G02 version).

Other equipment, via a mono 3.5mm jack output (centre pin hot) that provides 12VDC (8VDC on G02). It is always low in standby. By default it is high for all sources, so can be used to bring a G56 or G57 Two-channel Power Amplifier out of standby. Alternatively you can program it to be high for specific sources; eg to control a projection screen.

To connect to other Meridian G Series, 500 Series, or 800 Series equipment

In a system of Meridian products the products should be linked together in a chain, via the COMMS sockets, using the Comms leads supplied with each product. The sequence in which you connect the units is not important.

One of the products acts as the controller for the system, receiving infra-red commands from the MSR+, and then, if appropriate, relaying them to the other products via the Comms link. The following procedure should be used to set up the Comms correctly between several products:

- Switch all the units to standby.
- Press **Clear** (MSR+).

Each unit will display:

Auto

One unit will then be designated as the controller, and display:

Con.

All the other units will be configured as non-controllers, and display:


Not Con.

The system is now ready for use.

If the automatic setup does not work, first make sure you are operating the MSR+ from a position where all the units can receive the infra-red, and try again. Then:

- Check that none of the units have been configured to be IR Controller; see *Other settings*, page 22. Either all products should be set to Auto, or one should be configured as Controller and the others as Not Controller.

Note: Do not, under any circumstances, connect any equipment other than Meridian G Series, 500 Series, or 800 Series to any socket marked COMMS on the back of the product.

To connect FM and AM antennae (products fitted with AM/FM tuner)

- Connect an FM antenna or split-flex dipole to the FM Coax connector, if necessary using the adaptor provided.

In the UK use a female Belling-Lee (VCR) connector.

Although the FM tuner is very sensitive, the FM antenna is supplied for basic installation only, and for best performance and lowest noise use a high-quality antenna placed as high as possible and oriented towards the transmitter.

Note: For all outdoor antennae we strongly recommend you use a qualified installer who will comply with local safety regulations.

- Connect an AM antenna to the AM connector by pressing the tabs and inserting a bare wire into each hole. The ground connection (black on the supplied AM antenna) should be connected to the socket marked GND.


The product is supplied with an indoor loop antenna. This is directional, and for best results you will need to orient it, and this may be station dependent.

- Place the antenna as far away from other electrical equipment and as high as possible.

For best AM results use an external AM antenna.

Note: For AM you must fit a good ground as well as an antenna.

The tuner can be used with most proprietary indoor AM, FM, or combi (AM/FM) antennae. It is possible in some cases to use a trigger output from the product to power such devices. For more details, look at the Library/Applications sections of the Meridian web site at www.meridian-audio.com/lib-apps.htm.

To connect DAB and FM antennae

The DAB/FM tuner uses a single antenna input for both DAB and FM reception. For optimum reception we recommend using both DAB and FM antennae with an appropriate combiner.

For DAB-only listening the supplied DAB antenna may be sufficient. However, in many areas an external or loft mounted DAB antenna will be needed to receive all the available stations. This should either be a dipole aerial or a four-element aerial.

For FM reception, consult a professional aerial installer for information about the recommended type to use in your area.

In the UK aerials should be mounted with all elements vertical as the DAB transmissions are vertically polarised.

The DAB antenna should be connected to the antenna input using high-quality 50 Ω cable.

Configuring the control unit or receiver

This chapter explains how to configure the control unit or receiver using the Configuration Wizard.

Alternatively, for complete control over all aspects of the product’s configuration you can set up the unit from a computer using the Meridian Configuration Program. For full information refer to the *Meridian Configuration Program Guide* available separately.

Configuration Wizard

The **Configuration Wizard** leads you through the correct sequence to configure your control unit or receiver. Alternatively, you can skip between the configuration stages, which allow you to reset the configuration, or configure the sources or other settings of the control unit or receiver.

To run the Configuration Wizard


- If necessary press **On/Off** to put the control unit or receiver into standby.
- Press **More**.

If the product is locked the display shows:



- Press **Unlock** to unlock it, then press **More**.

The displays then shows:



- Press **Wizard**.

Follow the sequence of configuration stages described in the following pages, pressing **Next** to proceed after completing each stage.

At any stage in the Configuration Wizard the following options are available:

To do this	Press
Go back to an earlier configuration option	Back
Return to the title screen for the stage	Home
Exit from the configuration menus	On/Off
Display help about the current option	More

Stage 1: Resetting the product

The control unit or receiver provides several alternative standard settings, called Types, which configure all aspects of the product into the most commonly needed configurations.

Choosing one of the Types overrides any other configuration you may have performed, and so can be used to reset the configuration of the unit.

To reset the configuration

- Press **Wizard**.

The display shows the title screen for stage 1:



- Press **Next** to proceed or **Skip** to go stage 2.

If you pressed **Next** the display shows:



- Press **Yes** to proceed or **Back** to exit.

The display shows the current Type:



- Press **▲** or **▼** to step through the available Types.

A description of each type is shown on the top line of the display. As you select each Type the control unit or receiver is reset to that Type.

When you have selected the Type you want:

Either:

- Press **Next** to proceed to configuring sources, as described in the next section.

Or:

- Press **On/Off** to return to standby.

Types

The following table lists the available types:

Type	Description
Type 1	Main system.
Type 2	Second zone system.

Stage 2: Configuring sources

The control unit or receiver provides up to 12 sources corresponding to the 12 source keys on the MSR+:

CD, RADIO, DVD, AUX, DISC, TAPE, TV, CABLE, SAT, VCR1, VCR2, GAME.

For each source the **Configure sources** stage allows you to configure:

- Whether it is in use.
- The label used for it on the front-panel display, of up to five characters.
- The audio input it selects.
- The TRIGGER output level it selects.
- The Comms type and address, to identify other Meridian equipment.

The procedure for doing this is as follows.

To configure a source

Either:

- Press **Next** after resetting the product; see page 18.

Or:

- Press **Wizard**; see page 17.
- Press **Skip** to skip past the **Reset settings** menu.

The display shows the title screen for stage 2:



- Press **Next** to proceed or **Skip** to go to stage 3.

The display shows the first source and the first configuration option for that source: whether it is in use:



- Press **Next** or **Back** to step between options.

A description of each option is shown on the top line of the display, and its current value is shown to the right of the source name.

When changing the source name, **Next** and **Back** step between character positions.

The options are summarised in the table on the next page.

To change an option

- Press **▲** or **▼** to step through the alternative values for the option.

To move to the next source

- Press **Source**.

When you have finished configuring sources:

Either:

- Press **Next** on the last option of the last source (Game) to proceed to configuring settings, as described in the next section.

Or:

- Press **On/Off** to return to standby.

Source options

The following table summarises the source options:

Option	Values	Description
in use	in use, not in use	Whether the source is enabled.
Audio Input	A1-A7, Tuner (not G02), Last Valid*	The audio input used for the source.
Source Name		Any name of up to five characters.
Trigger	Low, High	Trigger output for the source.
Comms Type	CD 1C, Tuner 2C, DVD 3C, 4C-8C, No Comms NC	The type of Meridian product that the source is.
Comms Address	1A-8A	Allows you to individually control up to eight identical sources.

*A1-A7 correspond to the seven analogue inputs. Tuner corresponds to the internal tuner. Last Valid means that selecting the source will not switch the input, but leave it set to the last valid input choice.

Stage 3: Configuring other settings

The final stage allows you to configure other aspects of the product’s operation.

To configure other settings


Either:

- Press **Next** after configuring the sources; see page 19.

Or:

- Press **Wizard**; see page 17.
- Press **Skip** to skip past the **Reset settings** and **Configure sources** stages.

The display shows the title screen for stage 3:



- Press **Next** to proceed.

The first setting is displayed:



A description of each setting is shown on the top line of the display, and its current value is shown to the right of the display.

The settings are summarised in the table on the next page.

To change a setting

- Press ▲ or ▼ to step through the alternative values for the setting.

When you have finished configuring the settings:

- Press **Next** to complete the Wizard.

The display shows:



Either:

- Press **Exit** to return to standby.

Or:

- Press **Restart** to return to stage 1; see page 18.

Other settings

The following table summarises the product settings:

Option	Values	Description
Tuner region (not G02)	Europe, USA, Japan*	Band selection (MW/LW or AM), tuning steps, and FM deemphasis standard. For all countries except the USA use the Europe setting.
DAB band	Band III, L Band, Canada, Band III + L Band, Band III + Canada	DAB band selection, varies locally; please check with your dealer.
IR Controller?	Auto, Controller, Not Controller	Whether the product is the infra-red controller for the system.
Main System Address	1-8	Advanced setting.
Copy System Address	1-8	Advanced setting.
Product Address	1-8	Advanced setting.

* Japan option not available with DAB/FM tuner.

Configuring the sensitivity of each source

You can adjust the sensitivity of each source to accommodate differences in their levels.

To adjust the sensitivity of the current source

- Unlock the product; see *Configuration Wizard*, page 17.
- Select the analogue source you want to adjust.
- Press **More** until the **Gain** command is displayed.
- Press **Gain**.

The display shows the available sensitivities:



CD	65			
0.5V	1V	1.4V	2V	2.8V

- Choose the sensitivity for the source.
- Press **Home** to exit.

Troubleshooting

We expect you to achieve superb results with the control unit or receiver. If, however, you encounter any problems, either when installing and configuring it, or during operation, please check the following pages for suggested solutions.

If these suggestions fail to cure the problem, please contact your Meridian dealer for further assistance.

General operating problems

No blue light is displayed when switching on

- Check that the AC power supply is connected correctly.
- Check that the **ON OFF** switch on the back panel is in the **ON** position.
- Check that the fuse on the product’s back panel and the fuse in the unit’s power plug have not blown; see *To change the mains fuse*, page 28.

There is no sound (G51)

- Check the jumpers are fitted between the preamplifier outputs and power amplifier inputs.

The sound has cut out and there is no display (G51)

The G51 Receiver includes electronic protection, which will protect the output if the connections are accidentally shorted.

The amplifier may have tripped the mains due to a source with an excessive DC level.

- Unplug the source.
- Turn off the power, and then turn it on again.

If this restores normal operation check the source. Otherwise there may be a fault with the receiver, and you should consult your dealer.

The sound has cut out and the display shows Hot (G51 only)

This indicates that the power amplifier stage of the receiver has turned off due to overheating.

- Allow the receiver to cool down.

If the problem continues to occur there may be a fault with the receiver, and you should consult your dealer.

Communication is not working between the G01/G02/G51 and other Meridian products

- Check that all products are interconnected using the correct Comms leads.
- Ensure that one of the products is the controller; see *To connect to other Meridian G Series, 500 Series, or 800 Series equipment*, see page 14.
- If the problem continues, reset the product; see *Stage 1: Resetting the product*, page 18. **Warning:** All settings will be lost.

There is hum

- Check your other equipment.
- For turntables, check the TECHNICAL GROUND connection.
- If you are using the G51 PRE OUT/AMP IN loop with a third-party surround controller or other product, ensure that the third-party product is properly earthed or bonded to the TECHNICAL GROUND of the G51.
- If you are unable to cure the problem consult your dealer.

FM tuner problems**FM tuner reception is poor**

To obtain high-quality stereo reception on FM a good aerial is essential. Try positioning the antenna at different points in a room; generally performance is best high up and near a window.

In some areas a fixed antenna installation will be necessary. This can be placed in a loft or mounted externally.

Note: For all outdoor antennae we strongly recommend you use a qualified installer who will comply with local safety regulations.

RDS station names are not being received

Not all stations transmit the station name in all areas.

If the station name is not available you can define a preset station with a name; see the *G Series System Guide*.

AM tuner problems**AM tuner reception is poor**

Position the antenna to maximise the strength of the station you want to receive and to reduce interference from other stations on nearby frequencies.

Position the antenna away from items that generate electrical interference, such as fluorescent tubes and televisions.

DAB tuner problems

The display shows “No signal”

This indicates that the tuner cannot locate a signal for the selected service.

- Check that the antenna is connected correctly and reselect a service.

You may need to use a better aerial.

This may also indicate that a stored ensemble is no longer available, either because the tuner has been moved to a different area of the country, or because the transmission has ended.

- Perform a scan to rebuild the list of services.

The display shows “Weak signal”

This indicates that the reception is poor.

- Try moving the aerial to improve reception, or fit a better aerial.

The display shows “No Services”

This indicates that a list of available services has not been built.

- Perform a scan to build a list of available services.

Maintenance

Cleaning

To clean the case, display panel, and keypad

- Disconnect the power cord before cleaning the unit.

The exterior surfaces of Meridian G Series products are made from solid anodised aluminium, powder coated steel, thermoplastic rubber, and glass.

They are designed to be easily wiped clean with a dry, lint free cloth. Greasy marks should be removed by light rubbing with a slightly damp cloth and a trace of proprietary glass cleaner. Do not use any other solvent or abrasive based cleaners. Dust can be removed from the disc drive tray with a small dry brush when the drawer is open.

Ensure that no liquid enters the casework and that the product is completely dry before re-connection.

To clean the audio connections

The audio sockets on the back of the product are gold plated and do not need to be cleaned if gold-plated plugs are used. Otherwise, it is recommended that you unplug and reconnect the plugs at least once a year. A proprietary contact cleaner can be used to some advantage.

To change the mains fuse

- Remove the mains connector, and pull out the drawer above the power input to access the fuse.

Before replacing a blown fuse, it is best to ascertain the cause of the failure.

The fuse drawer includes a spare fuse. This should be replaced by a fuse of the same rating.

Service and guarantee

Service

The Meridian G Series of hi-fi components has been carefully designed to give years of untroubled service. There are no user-serviceable parts inside the case, nor do the units require any form of maintenance.

In the unlikely event that your product fails to function correctly, it should be returned, in its original packaging, to your Meridian dealer.

In case of difficulty within the UK or USA please contact the appropriate sales and service address shown on page iv.

In case of difficulty outside the UK or USA, contact the importing agent for the territory. A list of Meridian agents outside the UK is available from Meridian Audio.

No responsibility can be accepted for the product whilst in transit to the factory or an agent, and customers are therefore advised to insure the unit. When seeking service under guarantee, proof of the date of purchase will be required.

Guarantee

The product is guaranteed against defects in material and workmanship for two years from the date of purchase.

The guarantee is void if the product has been subject to misuse, accident, or negligence, or has been tampered with or modified in any way without the written authorisation of Meridian Audio Limited. **Note:** Connecting anything other than the correct network lead to the Comms sockets may cause damage to the product which will not be covered by this guarantee. Attempted servicing by unauthorised people may also invalidate this guarantee. Labour and carriage charges are not covered unless by local agreement.

Outside the UK, local warranty liability is restricted to equipment purchased within the territory. Our agents outside the UK are only under contractual obligation to service under-guarantee equipment sold through them. They are entitled to make a non-refundable charge for any service carried out on other equipment.

This guarantee does not limit your statutory rights within the country of purchase.

30		
Troubleshooting		

A

accessories 5
AM antenna 5, 15
AM reception 15, 26
antenna, connecting 15, 16
automatic setup 14

C

cleaning 28
COMMS, connecting 14
configuration, resetting 18
Configuration Wizard 17
configuring
 settings 21
 sources 19
 source sensitivities 23
connections
 audio 6
 cleaning 28
 communications 13
Controller, setting 14

D

DAB antenna 5, 16
DAB reception 16, 27

F

FM antenna 5, 15, 16
FM reception 15, 26

G

G01 Control Unit 1
 audio connections 6
 specifications 4
G02 Balanced Control Unit 1
 audio connections 7
 specifications 4
G07, connecting to 9
G08, connecting to 9
G51 Receiver 1
 audio connections 8
 specifications 4
guarantee 29

L

loudspeakers, connecting to 12

M

M33 loudspeakers, connecting to 11
mains fuse, changing 28
models 1

R

resetting the product 18

S

safety warnings ii
second-zone system, connecting 11
sensitivity of sources, adjusting 23

32		
Index	<div data-bbox="300 300 503 430">settings, configuring 21 sources, configuring 19 source options 20 specifications 4</div> <div data-bbox="894 300 1162 479">T tape recorder, connecting to 10 troubleshooting 25 turntable, connecting to 10 Types 18</div>	